

# EHO30

## ON-PREMISE E-SERIES SOFT-MOUNT WASHER-EXTRACTOR

Capacity <i>lbs</i>	30
Cylinder Diameter <i>inch</i>	24.4
Cylinder Depth <i>inch</i>	16.4
Cylinder Volume <i>cu ft</i>	4.4
Net Weight <i>lbs</i>	758
Crated Weight <i>lbs</i>	820
Machine Dimensions <i>inch</i> WxDxH	31.3 x 34.9 x 52.2
Door Opening <i>inch</i>	12.9
Floor to Door <i>inch</i>	20
Shipping Dimensions <i>inch</i> WxDxH	32.4 x 37.2 x 58.5
Washing Speed <i>rpm</i> Logi Control Inteli Control	48 17/23/30/37/44
Spin Speeds <i>rpm</i>	48/100/400/600/800/1000
G-force	0.8/3.46/56/125/222/346
Static Force Transmitted <i>lbs</i>	902
Dynamic Force Transmitted <i>lbs</i>	201
Frequency of Dynamic Force <i>Hz</i>	16.7
Available Voltages/Wire Conductor/Amp Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional)	208-240/60/1, 2W+G, 10 208/60/1, 2W+G, 40 240/60/1, 2W+G, 50 208-240/60/3, 3W+G, 40
Modified Energy Factor (MEF)	2.08
Water Consumption Factor (WCF)	4.68
Drain Diameter <i>inch</i>	3
Water Inlets <i>inch</i>	2 @ 3/4
Recommended Water Pressure <i>PSI</i>	30-60
Water Flow <i>gal/min</i>	16
Steam Connection <i>inch</i>	1/2
Steam Pressure (optional) <i>PSI</i>	29-87
Steam Flow (optional) <i>lbs/h</i>	176
Total Power <i>kW</i>	0.87
Electrical Heating Power (optional) <i>kW</i> Single Phase 240V Three Phase 240V	8.4 12.4

\* Specifications subject to change without notice or obligation. Contact Continental Girbau at (800) 256-1073 for dimensions not shown or for clarification.

\* Modified Energy Factor (MEF) measured in cubic feet per kilowatt-hour per cycle. Water Consumption Factor (WCF) measured in gallons per cycle per cubic feet. MEF and WCF statistics are according to DOE test results report by Intertek, an independent testing laboratory, dated February 27, 2007.

