

EH080

VENDED EXPRESSWASH SOFT-MOUNT WASHER-EXTRACTOR

ARCHITECTURAL/MECHANICAL
PRODUCT SPECIFICATIONS

ExpressWash

Capacity <i>lbs</i>	80
Cylinder Diameter <i>inch</i>	32.5
Cylinder Depth <i>inch</i>	23.5
Cylinder Volume <i>cu ft</i>	11.3
Net Weight <i>lbs</i>	1499
Crated Weight <i>lbs</i>	1583
Machine Width <i>inch</i>	41.5
Machine Depth <i>inch</i>	50.9
Machine Height <i>inch</i>	59.1
Door Opening <i>inch</i>	16.8
Floor to Door <i>inch</i>	23.6
Shipping Dimensions <i>inch</i> WxDxH	42.3 x 52 x 65.2
Washing Speeds <i>rpm</i>	42
Spin Speeds <i>rpm</i>	83/335/530/698/931
G-force	3.17/52/130/225/400
Static Force Transmitted <i>lbs</i>	1850
Dynamic Force Transmitted <i>lbs</i>	412
Frequency of Dynamic Force <i>Hz</i>	15.5
Available Voltages / Wire Conductor / Amp	
208/60/3	3W+G, 15 Amp
240/60/3	3W+G, 15 Amp
440-480/60/3	3W+G, 10 Amp
Drain Diameter <i>inch</i>	3
Water Inlets <i>inch</i>	2 @ 3/4
Recommended Water Pressure <i>PSI</i>	30-60
Water Flow <i>gal/min</i>	16
Total Power <i>kW</i>	4.2
Electric Heating Power <i>(optional) kW</i>	20.7

* Specifications subject to change without notice or obligation. Contact Continental Girbau at (800) 256-1073 for dimensions not shown or for clarification.

