

EH070

ON-PREMISE E-SERIES SOFT-MOUNT WASHER-EXTRACTOR

Capacity <i>lbs</i>	70
Cylinder Diameter <i>inch</i>	32.5
Cylinder Depth <i>inch</i>	20.9
Cylinder Volume <i>cu ft</i>	9.9
Net Weight <i>lbs</i>	1401
Crated Weight <i>lbs</i>	1484
Machine Width <i>inch</i>	41.5
Machine Depth <i>inch</i>	52
Machine Height <i>inch</i>	59.1
Door Opening <i>inch</i>	16.8
Floor to Door <i>inch</i>	23.6
Shipping Dimensions <i>inch</i> WxDxH	42.3 x 52 x 65.2
Washing Speeds <i>rpm</i>	16/21/26/36/42
Spin Speeds <i>rpm</i>	83/335/530/698/937
G-force	3.17/52/130/225/405
Static Force Transmitted <i>lbs</i>	1790
Dynamic Force Transmitted <i>lbs</i>	403
Frequency of Dynamic Force <i>Hz</i>	15.5
Available Voltages / Wire Conductor / Amp	
Hot Water (standard)	208-240/60/1, 2W+G, 20
Electric Auxiliary Heat (optional)	208-240/60/1, 2W+G, 20
Hot Water (standard)	208-240/60/3, 3W+G, 10
Electric Auxiliary Heat (optional)	208/60/3, 3W+G, 60
Electric Auxiliary Heat (optional)	240/60/3, 3W+G, 60
Steam Auxiliary Heat (optional)	208-240/60/3, 3W+G, 10
Drain Diameter <i>inch</i>	3
Water Inlets <i>inch</i>	2 @ 3/4
Recommended Water Pressure <i>PSI</i>	30-60
Water Flow <i>gal/min</i>	16
Steam Connection <i>inch</i>	1/2
Steam Pressure (optional) <i>PSI</i>	29-87
Steam Flow (optional) <i>lbs/h</i>	176
Total Power <i>kW</i>	3.0
Electric Heating Power (optional) <i>kW</i>	20.7

* Specifications subject to change without notice or obligation. Contact Continental Girbau at (800) 256-1073 for dimensions not shown or for clarification.

