

# RMG040

## ON-PREMISE G-FLEX HARD-MOUNT WASHER-EXTRACTOR

ARCHITECTURAL/MECHANICAL  
PRODUCT SPECIFICATIONS

Capacity <i>lbs</i>	40
Cylinder Diameter <i>inch</i>	24.4
Cylinder Depth <i>inch</i>	21.6
Cylinder Volume <i>cu ft</i>	6
Net Weight <i>lbs</i>	562
Crated Weight <i>lbs</i>	624
Machine Dimensions <i>inch</i> WxDxH	29.5 x 41.8 x 52.9
Door Opening <i>inch</i>	12.9
Floor to Door <i>inch</i>	20
Shipping Dimensions <i>inch</i> WxDxH	30.6 x 43.1 x 58.8
Washing Speed <i>rpm</i>	47
Spin Speed <i>rpm</i>	47/100/380/540/635/760
G-force	50/100/140/200
Static Force Transmitted <i>lbs</i>	805
Dynamic Force Transmitted <i>lbs</i>	1828
Frequency of Dynamic Force <i>Hz</i>	12.7
Available Voltages/Wire Conductor/Amp	208-240/60/1, 2W+G, 10
Drain Diameter <i>inch</i>	3
Water Inlets <i>inch</i>	2 @ 3/4
Recommended Water Pressure <i>PSI</i>	30-60
Water Flow <i>gal/min</i>	16
Steam Connection <i>inch</i>	1/2
Total Power <i>kW</i>	0.8

\* Specifications subject to change without notice or obligation. Contact Continental Girbau at (800) 256-1073 for dimensions not shown or for clarification.

