CG85-955 CG-SERIES UP TO 95-POUND CAPACITY DRYER

| ARCHITECTURAL/MECHANICAL |
|--------------------------|
| PRODUCT SPECIFICATIONS |

| Capacity <i>lbs</i> | up to 95 |
|---|--|
| Cylinder Diameter inch | 37 |
| Cylinder Depth inch | 37.4 |
| Cylinder Volume cu ft | 23.3 |
| Net Weight <i>Ibs</i> | 850 |
| Crated Weight <i>Ibs</i> | 901 |
| Machine Dimensions <i>inch</i> (WxDXH) Gas/Electric Steam | 39.4 x 52.9 x 72 39.4 x 52.9 x 73.2 |
| Door Opening inch | 28 |
| Floor to Door <i>inch</i> | 27.4 |
| Shipping Dimensions <i>inch</i> WxDxH | 40.6 x 57.1 x 78.1 |
| Drum Motor Power Hp | 1.14 |
| Extraction Motor Power Hp | 0.74 |
| Exhaust Diameter inch | 7.9 |
| Exhaust Air Flow <i>cfm</i> | 825.2 |
| Electric Heating <i>kW</i> | 30.8 |
| Gas Connection inch | 1/2 NPT |
| Gas Heating BTU/h | 147,781 |
| Steam Connection <i>inch</i> Inlet Outlet | 3/4 NPT 1/2 NPT |
| Steam Heating <i>BTU/h</i> at 130 PSI | 145,596 |
| BHP Consumption <i>BHP</i> at 130 PSI | 3.48 |
| Available Voltages/Wire Conductor/Amp (Rev Amp) | |
| Gas/Steam | 200-240/60/1, 2W+G, 10 200-240/60/3, 3W+G, 10 200-240/50/1, 2W+G, 10 380-415/60/3, 4W+G, 10 |
| Electric | 200-240/60/3, 3W+G, 100 380-415/60/3, 4W+G, 63 |

* Specifications subject to change without notice or obligation. Contact Poseidon Textile Care at (800) 256-1073 for dimensions not shown or for clarification.







