

ED660

ARCHITECTURAL/MECHANICAL
PRODUCT SPECIFICATIONS

ED-SERIES UP TO 95-POUND CAPACITY TEXTILE CARE DRYER

Capacity <i>lbs</i>	up to 95
Cylinder Diameter <i>inch</i>	37
Cylinder Depth <i>inch</i>	37.4
Cylinder Volume <i>cu ft</i>	23.3
Net Weight <i>lbs</i>	850
Crated Weight <i>lbs</i>	901
Machine Dimensions <i>inch</i> (WxDXH)	
Gas/Electric	39.4 x 52.9 x 72
Steam	39.4 x 52.9 x 73.2
Door Opening <i>inch</i>	28
Floor to Door <i>inch</i>	27.4
Shipping Dimensions <i>inch</i> WxDxH	40.6 x 57.1 x 78.1
Drum Motor Power <i>Hp</i>	1.14
Extraction Motor Power <i>Hp</i>	0.74
Exhaust Diameter <i>inch</i>	7.9
Exhaust Air Flow <i>cfm</i>	825.2
Electric Heating <i>kW</i>	30.8
Gas Connection <i>inch</i>	1/2 NPT
Gas Heating <i>BTU/h</i>	147,781
Steam Connection <i>inch</i>	
Inlet	3/4 NPT
Outlet	1/2 NPT
Steam Heating <i>BTU/h</i> at 130 PSI	145,596
BHP Consumption <i>BHP</i> at 130 PSI	3.48
Available Voltages/Wire Conductor/Amp (Rev Amp)	
Gas/Steam	200-240/60/1, 2W+G, 10
	200-240/60/3, 3W+G, 10
	200-240/50/1, 2W+G, 10
	380-415/60/3, 4W+G, 10
Electric	200-240/60/3, 3W+G, 100
	380-415/60/3, 4W+G, 63

* Specifications subject to change without notice or obligation. Contact Poseidon Textile Care at (800) 256-1073 for dimensions not shown or for clarification.

